



BIO DIGEST AIDE

ENZYME PRODUCING NON-PATHOGENIC AEROBIC & ANAEROBIC BACTERIA

- * Fast Acting
- * Liquefies Grease
- * Contains No Acid
- * Multiple Strains of bacteria
- * Non-toxic
- * Bleach Resistant
- * Eliminates Odors

CAUTION: Keep out of reach of children.

48B40 Net Contents: 1 GALLON

This product contains multiple strains of non-pathogenic bacteria that produce enzymes necessary for degradation of soils, organic oils and food by-products from grease traps, septic tanks, downpipes, drain lines, portable toilets, recreational vehicles, sump pumps, marinas, wet wells. Reduces odors and suspended solids. Contains no acid or caustics and is non-polluting. This product can also be used after treatment with sulfuric acid drain openers to prevent future clogging and residual hydrogen sulfide odors.

DIRECTIONS FOR USE:

DRAIN LINES AND DOWN PIPES: Use 2 times weekly, to maximum of 4 times depending on the usage of the building. Add product in amounts listed below, start on the lowest floor and work up at the rate of one floor per day. Do not treat the floor twice. When the top floor is reached continue treatment for the top floor only. Dosage by pipe size: 2" use 4 oz., 4" use 8 oz., 6" use 12 oz., 8" use 16 oz. This product should be used after a sulfuric acid drain opener. This flushes the system completely, activates the natural digestive process, prevents future clogging and eliminates Hydrogen Sulfide fumes caused by Sulfuric Acid.

GREASE TRAPS: For traps with less than 20 cubic feet capacity, add 4-5 oz. daily by pouring in a sink or pipeline closest to the trap. This should be done at night or when the traps are used the least. After added, flush down with a cup of lukewarm water. For grease traps larger than 20 cubic feet, add 8-10 oz. daily using the same procedure.

RECREATIONAL VEHICLES AND BOATS: Add 2 oz. per gallon of water in hold tank. Thereafter use 1 oz. per gallon as needed. For use in a dump station, use 1 oz. per 50 gallons of tank capacity. Use one pint per week for maintenance.

RESTROOM: Remove as much solid matter as possible. Spray area where odor is originating, usually the urinals, toilets, carpets or floor and wall area around washroom.

PORTA-TOILETS: Add one gallon (4 quarts) directly. Cover the solids with water to aid digestion.

CAUTION: Keep out of reach of children. Do not take internally. Avoid getting in eyes or open wounds. Keep out of sunlight. Avoid exposure to extremely hot or boiling water, disinfectants or chlorinated compounds.

Manufactured By

PIC. INC.

P.O. BOX 161577 • FORT WORTH, TEXAS 76161
(800) 359-8031