

# FORMULA 3000 TOWER TREATMENT

## COOLING TOWER INHIBITOR FOR CONTROL OF CORROSION, SCALE & SLUDGE

\*Non Zinc Formula

\*Non Chromate Formula

**CAUTION:** Keep out of reach of children. Harmful if  
swallowed

<b>50B57</b>	<b>NET CONTENTS</b>	<b>GALLON(S)</b>
--------------	---------------------	------------------

Formula 3000 Tower Treatment is a highly effective scale and corrosion inhibitor that protects cooling tower and process equipment lines from harmful scale, sludge and corrosion. This product employs the newest technology using Co Polymers instead of Zinc or Chromates. It can be effectively used in open re-circulating cooling towers, lithium bromide units, evaporative condensers, humidifiers, air washers and once through cooling systems.

### **DIRECTIONS:**

Formula 3000 Tower Treatment may be added directly to the tower sump by hand or by the use of an injection system. For best results, clean system thoroughly, removing all algae, scale and corrosion before adding product. This compound should be fed at 200 to 300 ppm into cooling tower system. Test for presence of product in system by using a phosphate test kit. Maintain from 4 to 8 ppm residue in system water.

**CAUTION:** Harmful or fatal if swallowed. Avoid excessive exposure of concentrated product to skin or eyes. Store at room temperature.

### **TO REORDER:**

PIC

4408 Glenview Dr, Haltom City, TX 76117  
817-281-1474 \* 800-359-8031