
SUPER POWER PLUS may be added to the vehicle tank, or it can be added to the fuel in storage tanks. Pour SUPER POWER PLUS into vehicle or storage tank prior to filling. NOTE: 32 ounces of SUPER POWER PLUS to 250 gallons of #2 diesel fuel should protect fuel down to -24 degrees below zero. SUPER POWER PLUS is highly concentrated. It is specifically designed to overcome many of the problems associated with #2 diesel fuels. The package contains:

- *An anti-gel agent to lower cold temperature fuel pour point.
- *A flow improver which modifies the wax crystals.
- *An anti-oxidant to help control corrosion.
- *A water dispersant to eliminate condensation problems.
- *A detergent additive to clean injectors and pumps.
- *A biocide to control algae growth
- *Lubricity additive for engine protection.
- *Contains NO alcohols, methanols or benzene.

SUPER POWER PLUS

SUPER CONCENTRATED ANTI-GEL DIESEL FUEL CONDITIONER

1 TO 1000 -24 F PROTECTION



CAUTION:

Combustible liquid. Keep out of reach of children. Keep away from heat and flame. DO NOT DRINK. Flash point 100 F or higher. Do not take internally.

80L36 NET CONTENTS OUNCES

ADDITIONAL CAUTIONS:

EYES: Irritating but does not injure eye tissue. If contact occurs, flush with water until irritation subsides. If irritation persists, get medical aid.

SKIN: Frequent or prolonged contact may irritate and cause dermatitis. If contact occurs, wash with soap and water.

INHALATION: May be irritating to respiratory tract, may cause dizziness, collapse, muscle twitching, coma and later pneumonia. If inhaled, move to fresh air. Give CPR if unconscious and oxygen if needed once respiration is restored.

INGESTION: May cause nausea, vomiting and diarrhea. If ingested, DO NOT INDUCE VOMITING. Give water to dilute stomach contents. Keep warm and quiet. Seek medical aid.

TO REORDER:
PIC
4408 Glenview Dr
Haltom City, TX 76117
(817) 281-1474 (800) 359-8031